

Specifications

Length	24" (609.6mm~)
Core Thickness	3mm
Pieces Per Carton:	16 PIECES/CTN
SQ. Feet Per Carton:	32 SQFT/CTN
Weight Per Carton:	Tile 36.4LBS/CTN

Wear Layer	30mil (0.70mm)
Surface	UV/Ceramic Bead
Edge	Micro-Bevel 4 sides
Carton Per Pallet:	60 CTNS/PLT
SQ.Feet Per Pallet:	1920 SQFT/PLT

Testing Methods and Target Results

Test	Testing Method	Target Result
Abrasion (Wear Layer 0.5mm)	BS EN 13329	≥5000
Antiskid	DIN 51130	≥R9
Castor Chair Test	EN 425:2002	25000 Pass(without pad)
Critical radiant flux	ASTM E648-19a	1.05
Thickness	ASTM F1700-20	+/-0.20mm
Somke Density	ASTM E662-19	2.5±0.05 w/cm2
Sliding behaviour	EN 13893:2003	class DS
Airborne Sound Transmission	ASTM E90-23	STC 63
Impact Sound Transmission	ASTM E492-22	IIc 52
Flame Retardant Grade	EN 13501-1:2018-12	B-s1
Formaldehyde Content Test	SCS-EC10.3-2014 v4.1	Not Detected