



ComboFoam® is an Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications. As part of our *Value* Collection, ComboFoam is a fine choice for most Laminate, Engineered and Solid hardwood flooring installations. ComboFoam can be used in Floating and Nail down installations.

TYPICAL PHYSICAL PROPERTIES SHEET

GENERAL PROPERTIES

Item Name	ComboFoam®
Construction	Closed cell polyethylene
Overlap Options	Available with UltraSeal Self Sealing Lip & Tape
Thickness	2 mm
Coverage Area	100 sf
Standard Roll Size	46" wide x 26 lf
Product Grade	Value

PERFORMANCE

Impact Isolation Class (IIC)	up to (61) dB per ASTM E 492 / ASTM E 989
Sound Transmission Class (STC)	up to (54) dB per ASTM E 90
Moisture Vapor Transmission Rate	up to (2.0) lbs / 1000 ft² / 24 hr. per ASTM E 96
Compressive Strength @ 25%	≥ 3.5 psi per ASTM D 3575
Warranty Period	10 Years
Mold and Mildew Resistant	Yes
R Value	Adds R value to chilly floors
Volatile Organic Compounds (VOCs)	100% LDPE product - resilient, nonreactive
Recyclable	Yes

PACKAGING

Rolls / Carton	40
Cartons / Skid	4
Skids / TL	22
Rolls / TL	3,520
SF / Carton	4,000 sf
SF / Skid	16,000 sf
SF / TL	352,000 sf

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.



Diversified Industries
121 High Hill Road
Swedesboro, NJ 08085
is a proud member of the
MADE IN NEW JERSEY
Program



Let's Get Social



Value
GRADE